

## 1. Identification

Product Identifier: **Flex 20 Casting Rubber A Side**  
**Flex 50 Casting Rubber A Side**  
**Flex 60 Casting Rubber A Side**  
**Flex 70 Casting Rubber A Side**  
**Flex 80 Casting Rubber A Side**

Use: Component for Liquid Polyurethane Casting Rubber. For Industrial/Professional use only.

Manufacturer: Alumilite  
 315 E. North Street Kalamazoo, MI 49007 USA

Phone Number: +1 800-447-9344 (9 a.m. to 5 p.m. EST)

Emergency Phone: CHEMTREC 800-424-9300 or  
 +1 703-527-3887

E-mail: [info@alumilite.com](mailto:info@alumilite.com)

## 2. Hazards Identification

### GHS Classification:

Acute Toxicity - Inhalation Category 4  
 Skin Irritation Category 2  
 Eye Irritation Category 2A  
 Respiratory Sensitization Category 1  
 Skin Sensitization Category 1  
 Carcinogenicity Category 2  
 Specific Target Organ Toxicity Single Exposure Category 3  
 Specific Target Organ Toxicity Repeated Exposure Category 2

Label Elements: Danger



Contains polymeric methylenediphenyl diisocyanate (MDI).

### Hazard Phrases

H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H319 Causes serious eye irritation.  
 H332 Harmful if inhaled.  
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
 H335 May cause respiratory irritation.  
 H351 Suspected of causing cancer.  
 H373 May cause damage to organs (lungs and respiratory system) through prolonged or repeated exposure.

### Precautionary Phrases

P202 Do not handle until all safety precautions have been read and understood.  
 P260 Do not breathe vapors or mists.  
 P280 Wear protective gloves, protective clothing, eye protection, and face protection.  
 P284 In case of inadequate ventilation, wear respiratory protection.  
 P302+352 IF ON SKIN: Wash with plenty of soap and water.  
 P304+340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308+313 IF exposed or concerned: Get medical attention.  
 P403+233 Store in a well-ventilated place. Keep container tightly closed.  
 P501 Dispose of contents and container in accordance with local, regional and national regulations.

**Supplemental Information:** Individuals sensitized to isocyanates should discontinue use. Long-term overexposure to isocyanates may cause lung damage.

This is one part of a two-part system. Read and understand the hazard information on part B before using.

## 3. Composition/Information on Ingredients

Chemical Name	CAS #	%
Polymeric methylenediphenyl diisocyanate (MDI) (includes isomers and oligomers)	9016-87-9	30-50
Other ingredients are not classified as health and/or environmental hazards, and/or are present below cut-off/concentration limits.		

## 4. First-Aid Measures

**Eye Contact:** Rinse thoroughly with water for at least 15 minutes, holding the eyelids open to be sure the material is washed out. Get prompt medical attention.

**Skin Contact:** Remove contaminated clothing. Wash contact area thoroughly with soap and water. Get medical attention if irritation or symptoms of exposure develop. Launder clothing before re-use. Discard items that cannot be decontaminated.

**Inhalation:** Remove person to fresh air. Give artificial respiration if needed. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.

**Ingestion:** Do not induce vomiting unless directed to do so by medical personnel. Get medical attention.

**Most Important Symptoms/Effects:** Causes skin and eye irritation. Vapors/mists may cause respiratory irritation. May cause allergic skin and/or respiratory reaction in sensitized persons. Symptoms include skin rash, wheezing, shortness of breath and other asthma symptoms. Prolonged inhalation overexposure may damage the lungs and respiratory system.

**Indication of Immediate Medical Attention/Special Treatment:** Immediate medical attention is required for asthmatic symptoms or serious inhalation exposures. Respiratory symptoms, including pulmonary edema, may be delayed. Persons receiving significant exposure should be observed 24-48 hours for signs of respiratory distress. Persons sensitized to isocyanates should consult a physician regarding working with respiratory irritants or sensitizers.

## 5. Fire-Fighting Measures

**Extinguishing Media:** Use water fog, foam, carbon dioxide or dry chemical. Do not direct solid water stream into hot product, since it may cause violent steam generation or eruption.

**Specific Hazards:** Not classified as flammable. Product will burn under fire conditions.

**Special Protective Equipment & Precautions for Fire-Fighters:** Wear positive pressure, self-contained breathing apparatus and full-body protective clothing. Cool fire-exposed containers with water.

## 6. Accidental Release Measures

### Personal Precautions, Protective Equipment and Emergency

**Procedures:** Remove ignition sources. Clear non-emergency personnel from the area. Wear a respirator and protective equipment to prevent eye and skin contact. Ventilate area. Caution – spill area may be slippery.

**Methods and Materials for Containment and Cleanup:** Cover with inert absorbent material and collect into a container for disposal. Do not seal the container since carbon dioxide is generated on contact with moisture and dangerous pressure buildup can occur. Decontaminate floor

area with a mixture of water plus isopropyl alcohol (20%), household ammonia (10%) and detergent (2%).

## 7. Handling and Storage

**Safe Handling:** Avoid breathing vapors, aerosols and mists. Use with adequate ventilation. Avoid contact with the eyes, skin and clothing. Wash thoroughly after handling. Do not eat, drink or smoke in the work area. Keep container closed when not in use.

**Safe Storage:** Store indoors at 60 to 95°F (15-35°C). Store in original, unopened containers. Protect from atmospheric moisture and water since MDI reacts with water to form carbon dioxide leading to potentially dangerous pressure build up in sealed containers.

## 8. Exposure Controls/Personal Protection

### Occupational Exposure Limits:

Methylenediphenyl diisocyanate (MDI) 0.02 ppm (C) OSHA PEL  
0.005 ppm TWA ACGIH TLV

**Ventilation:** Use with adequate general or local exhaust ventilation to maintain exposure levels below the occupational exposure limits.

**Respiratory Protection:** In the absence of good ventilation, use an approved respirator with organic vapor cartridges. Respirator selection and use should be based on contaminant type, form and concentration. For higher exposures or in an emergency, use a supplied-air respirator.

**Skin Protection:** Wear impervious gloves (butyl/nitrile rubber).

**Eye Protection:** Wear chemical safety glasses/goggles.

**Other Protective Measures:** Wear impervious clothing to prevent skin contact and contamination of personal clothing. An eye wash facility and washing facility should be available in the work area. Follow applicable regulations and good Industrial Hygiene practice.

## 9. Physical and Chemical Properties

**Appearance:** Clear yellow/amber liquids

**Odor:** Slight musty

**Odor Threshold:** 0.4 ppm (MDI)

**pH:** Not applicable

**Melting Point:** No data available

**Boiling Point:** No data available

**Flash Point:** >200°C (392°F)

**Evap. Rate:** No data available

**Flamm. Limits:** No data available

**Vapor Pressure:** ≤0.0007 mm Hg @ 25°C (Literature for MDI)

**Vapor Density:** No data available

**Relative Density:** 1.0-1.1 @ 25°C

**Solubility:** Insoluble in water

**Partition Coefficient: n-octanol/Water:** Reacts with water

**Auto-Ignition Temp:** No data available

**Decomposition Temp:** No data available

**Viscosity:** 300-2,500 cP @ 25°C

## 10. Stability and Reactivity

**Reactivity:** Diisocyanates react with many materials and the rate of reaction increases with temperature. Reaction with water generates carbon dioxide and heat.

**Chemical Stability:** Stable under recommended conditions.

**Possibility of Hazardous Reactions:** Elevated temperatures can cause hazardous polymerization. Polymerization can be catalyzed by strong bases or water. Reaction with water generates carbon dioxide, and results in heat and pressure buildup in closed systems.

**Conditions to Avoid:** Avoid moisture and temperatures below 60°F and above 95°F to protect product integrity and prevent pressure build up in closed containers.

**Incompatible Materials:** Avoid contact with water, acids, bases, alcohols, strong oxidizers, and some metals (e.g., aluminum, zinc, brass, tin, or copper).

**Hazardous Decomposition Products:** Possibly isocyanate vapor, carbon monoxide, nitrogen oxides, and traces of hydrogen cyanide.

## 11. Toxicological Information

**Eye Contact:** Causes serious eye irritation. May cause temporary corneal injury.

**Skin Contact:** Causes skin irritation. May stain skin. Repeated skin contact may cause an allergic skin reaction (sensitization). Animal studies indicate that skin contact with isocyanates may play a role in respiratory sensitization.

**Inhalation:** At room temperature, vapors are minimal due to low volatility. Vapors or aerosols (e.g., generated during heating or spraying) may cause respiratory irritation and possibly pulmonary edema. May cause respiratory sensitization. For individuals sensitized to isocyanates, exposure may result in allergic respiratory reactions (e.g., coughing, wheezing, difficulty breathing).

**Ingestion:** Single oral dose toxicity is low. Ingesting large amounts may cause adverse gastrointestinal effects.

**Chronic Health Effects:** Repeated or prolonged exposure to isocyanates above exposure limits may cause an allergic sensitization of the respiratory tract causing an asthma-like response upon re-exposure. Repeated overexposure to isocyanates has been associated with decreased lung function. Repeated or prolonged dermal contact with this product may cause allergic skin sensitization in some individuals.

**Acute Toxicity Values:** For MDI: Oral rat LD50 >10,000 mg/kg; Skin rabbit LD50 >9,400 mg/kg; Inhalation rat LC50 0.49 mg/L/4 hr (aerosol)

**Germ Cell Mutagenicity:** Not classified as a mutagen, since genetic toxicity data on MDI are inconclusive. MDI was weakly positive in some in vitro studies; other in vitro studies were negative. Animal mutagenicity studies were predominantly negative.

**Carcinogenicity:** Lung tumors have been observed in laboratory animals exposed to respirable aerosol droplets of MDI/Polymeric MDI (6 mg/m<sup>3</sup>) for their lifetime. Tumors occurred concurrently with respiratory irritation and lung injury. Current exposure guidelines are expected to protect against these effects reported for MDI. MDI is not designated as a carcinogen by NTP, IARC, or OSHA.

**Reproductive Toxicity:** In laboratory animals, MDI/polymeric MDI did not cause birth defects; other fetal effects occurred only at high doses which were toxic to the mother.

**Specific Target Organ Toxicity:** Single Exposure: May cause respiratory irritation. Repeat Exposure: Tissue injury in the upper respiratory tract and lungs has been observed in laboratory animals after repeated excessive exposures to MDI/polymeric MDI aerosols.

## 12. Ecological Information

**Ecotoxicity:** Not classified as dangerous to aquatic organisms (LC50/EC50 >100 mg/L in most sensitive species.)

**Persistence and Degradability:** Not readily biodegradable.

**Bioaccumulative Potential:** Not expected to bioaccumulate.

**Mobility in Soil:** Movement is expected to be limited by its reaction with water forming predominantly insoluble polyureas.

## 13. Disposal Considerations

Dispose according to local, state and federal regulations. Upon exposure to moisture, product forms an inert, non-hazardous solid.

## 14. Transport Information

Not regulated for transport by any mode.

**Emergency Shipping Information:** Call CHEMTREC, 800-424-9300 or +1-703-527-3887

## 15. Regulatory Information

### U.S. FEDERAL REGULATIONS:

**CERCLA 103 Reportable Quantity:** Not subject to reporting under CERCLA. Some states have more stringent reporting requirements. Report all spills in accordance with local, state, and federal regulations.

### SARA TITLE III

**Section 311/312:** Acute Health, Chronic Health

**Section 313 Toxic Chemicals:** Contains the following chemicals subject to SARA Title III Section 313 Reporting requirements:

Diisocyanates Category (N120) 30-50%

**Section 302 Extremely Hazardous Substances (TPQ):** None

**EPA Toxic Substances Control Act (TSCA) Status:** Chemical substances in this product are listed on TSCA.

### STATE REGULATIONS:

**California Proposition 65:** These products do not contain substances known to the State of California to cause cancer and/or reproductive harm. [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## 16. Other Information

**Training Advice:** All personnel using/handling this product should be trained in proper chemical handling and the need for and use of engineering controls and protective equipment.

**Recommended Uses and Restrictions:** This product is intended for industrial or professional use only.

**SDS Revision Notes:** Removed Prop 65 warning, May 17, 2019; GHS Format, October 28, 2018

**Disclaimer:** The information contained herein is considered accurate; however, Alumilite makes no warranty regarding the accuracy of the information. The user must determine the suitability of the product for the intended use and accepts all risk and liability associated with that use.

## 1. Identification

Product Identifier: **Flex 50 Casting Rubber B Side**  
**Flex 60 Casting Rubber B Side**  
**Flex 70 Casting Rubber B Side**  
**Flex 80 Casting Rubber B Side**

Use: Component for Liquid Polyurethane Casting Rubber. For Industrial/Professional use only.

Manufacturer: Alumilite  
 315 E. North Street Kalamazoo, MI 49007 USA

Phone Number: +1 800-447-9344 (9 a.m. to 5 p.m. EST)

Emergency Phone: CHEMTREC 800-424-9300 or  
 +1 703-527-3887

E-mail: [info@alumilite.com](mailto:info@alumilite.com)

## 2. Hazards Identification

### GHS Classification:

Skin Sensitizer Category 1  
 Hazardous to the Aquatic Environment – Acute Hazard Category 2  
 Hazardous to the Aquatic Environment – Long-Term Hazard Category 2

Label Elements: Warning



Contains dimethylthiotoluenediamine.

### Hazard Phrases

H317 May cause an allergic skin reaction.  
 H401/411 Toxic to aquatic life with long-lasting effects.

### Precautionary Phrases

P261 Avoid breathing vapors/spray.  
 P272 Contaminated work clothing should not be allowed out of the work area.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves and eye protection.  
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
 P333 + P313 If skin irritation or rash occurs: Get medical advice or attention.  
 P391 Collect spillage.  
 P501 Dispose of contents and container in accordance with local, regional and national regulations.

**Supplemental Information:** May cause eye and skin irritation. This is one part of a two-part system. Read and understand the hazard information on Part A before using.

## 3. Composition/Information on Ingredients

Chemical Name	CAS #	GHS Classification	%
Dimethylthiotoluenediamine	106264-79-3	Acute Tox – Oral 4 Skin Sensitizer 1 Aquatic Tox Acute 1 Aquatic Tox Chronic 1	5-15
Exact concentrations are withheld as trade secret. Other ingredients are not classified as health, physical or environmental hazards, or are present below cut-off/concentration limits.			

## 4. First-Aid Measures

**Eye Contact:** Rinse thoroughly with water, holding the eyelids open to be sure the material is washed out. Remove contact lenses if safe and easy to do. Continue rinsing. Get medical attention if irritation persists.

**Skin Contact:** Remove contaminated clothing. Wash contact area thoroughly with soap and water. Get medical attention if irritation persists.

**Inhalation:** Remove person to fresh air. Get medical attention if symptoms persist.

**Ingestion:** Do not induce vomiting unless directed to do so by medical personnel. Get medical attention.

**Most Important Symptoms/Effects:** May cause an allergic skin reaction.

**Indication of Immediate Medical Attention/Special Treatment:** If product gets in eyes, immediately flush with water.

## 5. Fire-Fighting Measures

**Extinguishing Media:** Use water fog, foam, carbon dioxide or dry chemical. Do not use solid water stream. Solid stream of water into hot product may cause violent steam generation or eruption.

**Specific Hazards:** Not classified as flammable or combustible. Product will burn under fire conditions. Combustion products include oxides of carbon and nitrogen, oxides of sulfur, sulfuric acid, organic acids, and other toxic organic compounds.

**Special Protective Equipment & Precautions for Fire-Fighters:** Wear positive pressure, self-contained breathing apparatus and full-body protective clothing. Cool fire-exposed containers with water.

## 6. Accidental Release Measures

### Personal Precautions, Protective Equipment and Emergency

**Procedures:** Remove all ignition sources. Clear non-emergency personnel from the area. Wear appropriate protective clothing to prevent eye and skin contact and avoid breathing vapors. Caution – spill area may be slippery.

**Methods and Materials for Containment and Cleanup:** Cover with an inert absorbent material and collect into an appropriate container for disposal. Avoid releases to the environment. Report spills and releases as required to appropriate authorities.

## 7. Handling and Storage

**Safe Handling:** Use with adequate ventilation. Avoid contact with the eyes, skin and clothing. Wash thoroughly after handling. Do not eat, drink or smoke in the work area. Keep container closed when not in use.

**Safe Storage:** Store indoors at 60 to 95°F (15-35°C). Store in original containers. Avoid getting moisture into containers. Keep containers tightly closed.

## 8. Exposure Controls/Personal Protection

**Occupational Exposure Limits:** None apply.

**Ventilation:** Use with adequate general or local exhaust ventilation to minimize exposure.

**Respiratory Protection:** If ventilation is inadequate/poor, use a NIOSH-approved respirator with organic vapor cartridges. Respirator selection and use should be based on contaminant type, form and concentration. For higher exposures or in an emergency, use a supplied-air respirator.

**Skin Protection:** Wear impervious gloves, such as butyl rubber or nitrile rubber.

**Eye Protection:** Wear chemical safety glasses or goggles.

**Other Protective Measures:** Wear impervious clothing to prevent skin contact and contamination of personal clothing. An eye wash facility and washing facility should be available in the work area. Follow applicable regulations and good Industrial Hygiene practice.

## 9. Physical and Chemical Properties

**Appearance:** Liquid; color vary

**Odor:** No data available

**Odor Threshold:** No data available

**pH:** Not applicable  
**Melting Point:** No data available  
**Boiling Point:** No data available  
**Flash Point:** >176°C (350°F)  
**Evap. Rate:** No data available  
**Upper/Lower Flammability Limits:** No data available  
**Vapor Pressure:** <0.01 mm Hg @ 25°C  
**Vapor Density:** No data available  
**Relative Density:** 1.0-1.1 @ 25°C  
**Solubility:** Slightly soluble in water  
**Partition Coefficient: n-octanol/Water:** No data available  
**Auto-Ignition Temp:** No data available  
**Decomposition Temp:** No data available  
**Viscosity:** 500-1,500 cP @ 25°C

## 10. Stability and Reactivity

**Reactivity:** Not normally reactive.  
**Chemical Stability:** Stable under recommended conditions.  
**Possibility of Hazardous Reactions:** None known.  
**Conditions to Avoid:** Avoid excessive heat and exposure to sunlight. Avoid moisture.  
**Incompatible Materials:** Avoid contact with strong acids and strong oxidizing agents.  
**Hazardous Decomposition Products:** Thermal decomposition will generate oxides of carbon and nitrogen, oxides of sulfur, organic acids and/or other toxic organic compounds.

## 11. Toxicological Information

**Eye Contact:** May cause eye irritation.  
**Skin Contact:** May cause skin irritation.  
**Inhalation:** Vapors or mists may cause mild respiratory irritation.  
**Ingestion:** Not fully determined, but single oral dose toxicity is low. Ingesting large amounts may cause adverse gastrointestinal effects.  
**Chronic Health Effects:** Not fully determined.  
**Acute Toxicity Values:** Mixture has not been tested, but based on LD50 of ingredients and calculated LD50; product is not classified as acutely toxic. For dimethylthiotoluenediamine: Oral rat LD50 1515 mg/kg; Dermal rabbit LD50 >2000 mg/kg.  
**Skin Corrosion/Irritation:** Components are not classified as skin irritants.  
**Eye Damage/Irritation:** Components are not classified as eye irritants.  
**Respiratory Irritation:** Components are not classified as respiratory irritants.  
**Respiratory Sensitization:** Components are not classified as respiratory sensitizers.  
**Skin Sensitization:** Dimethylthiotoluenediamine ingredient was positive in the guinea pig assay for skin sensitization.  
**Germ Cell Mutagenicity:** Components are not classified as mutagens.  
**Carcinogenicity:** Components are not classified as carcinogens.  
**Reproductive Toxicity:** Components are not classified as reproductive toxins.  
**Specific Target Organ Toxicity:** No data available.

## 12. Ecological Information

**Ecotoxicity:** Based on the concentration of dimethylthiotoluenediamine, these products are classified as hazardous to the aquatic environment (Acute and Long-Term Category 2).  
For dimethylthiotoluenediamine: Oncorhynchus mykiss LC50 16.9 mg/L/96 hr; Daphnia EC50 0.9 mg/L/48 hr.  
**Persistence and Degradability:** No data available.  
**Bioaccumulative Potential:** No data available.  
**Mobility in Soil:** No data available.

## 13. Disposal Considerations

Dispose according to local, state and federal regulations. In the U.S., upon disposal, these products (uncured or cured) are not RCRA hazardous waste as defined in 40 CFR 261.

## 14. Transport Information

**US Ground Transport:** Not regulated as a hazardous material by US DOT (49 CFR 171).  
**International:** UN3082, Environmentally hazardous substance, liquid, n.o.s. (Dimethylthiotoluenediamine), 9, III.  
**Emergency Shipping Information:** CHEMTREC, 800-424-9300 or +1-703-527-3887

## 15. Regulatory Information

**U.S. FEDERAL REGULATIONS:**  
**CERCLA 103 Reportable Quantity:** This product is not subject to reporting under CERCLA. Some states have more stringent reporting requirements. Report all spills in accordance with local, state, and federal regulations.  
**SARA TITLE III**  
**Section 311/312:** Acute Health, Chronic Health  
**Section 313 Toxic Chemicals:** This product does not contain chemicals subject to SARA Title III Section 313 Reporting requirements.  
**Section 302 Extremely Hazardous Substances (TPQ):** None  
**EPA Toxic Substances Control Act (TSCA) Status:** All components are listed on the TSCA inventory.

### STATE REGULATIONS:

**California Proposition 65:** These products do not contain substances known to the State of California to cause cancer and/or reproductive harm. [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## 16. Other Information

**Training Advice:** All personnel using/handling this product should be trained in proper chemical handling and the need for and use of engineering controls and protective equipment.  
**Recommended Uses and Restrictions:** This product is intended for industrial/professional use only.  
**SDS Revision Notes:** Update Prop 65, May 17, 2019; GHS Format, October 28, 2018  
**Disclaimer:** The information contained herein is considered accurate; however, Alumilite makes no warranty regarding the accuracy of the information. The user must determine the suitability of the product for the intended use and accepts all risk and liability associated with that use.